

# SPECTRA PRECISION®

## NOMAD™ DATA COLLECTOR

## SPECSHEET

### STANDARD FEATURES

- Windows Mobile 6.1 (Professional in WWAN models; Classic in all other models)
- Marvell 806 MHz XScale processor
- 128 MB DDR SDRAM
- 512 MB to 2 GB non-volatile internal flash storage
- Full VGA touchscreen display, sunlight-readable color TFT
- Environmentally rugged design
- Integrated speaker and microphone
- Integrated Bluetooth 2.0
- Secure Digital (SD/SDHC) slot
- Numeric style keypad
- Notification LEDs
- USB host and client
- Audio jack
- 15-hour battery life with active use (default settings)
- Keypad backlighting for night use
- 12-month limited warranty

### CONFIGURATION OPTIONS

- Integrated WWAN Quad-band GSM GPRS/EDGE capability
- Integrated GPS (SiRFstarIII, WAAS Capable, SiRFInstantFixII)
- Integrated WLAN Wi-Fi wireless capability
- CompactFlash (CF) (Type II) slot (on 900B model only)
- Integrated digital camera (color, 5 megapixel resolution, with flash)

### STANDARD SOFTWARE

- Microsoft Office Mobile
  - Word Mobile
  - Excel Mobile
  - PowerPoint Mobile
  - Outlook Mobile
  - Pocket OneNote
- Internet Explorer Mobile
- Notes/Tasks
- Calculator
- Windows Media Player
- Microsoft Pictures and Videos
- Online help
- Contacts/Calendar
- Microsoft ActiveSync®

### STANDARD ACCESSORIES

- Rechargeable Li-Ion battery module
- Hand strap
- Stylus lanyard
- Getting Started CD with ActiveSync
- USB boot
- Rugged stylus with spring-loaded tip
- User's guide
- International AC charger
- Screen protectors
- USB data cable

### PHYSICAL

Size . . . . . 17.6 cm x 10.0 cm x 5.0 cm (6.92 in x 3.92 in x 1.96 in)  
Weight . . . . . 596 g (21oz) including rechargeable battery

### CERTIFICATIONS

FCC, CE/R & TTE, IC (Canada), C-Tick, RoHS Compliant, PTCRB, GCF Compliant, AT&T network compatible, Section 508 compliant, CCX v4, MIL-STD-461E RE102, MIL-STD-461E RS103



### ENVIRONMENTAL SPECIFICATIONS

#### Meets or exceeds:

Sand & dust . . . . .	MIL-STD-810F, Method 510.3, Procedures I, II IEC-529, IP67
Water . . . . .	Immersed in 1 m (3.28 ft) of water for 30 minutes Water Jet 12.5 mm (0.49 in) dia. @ 2.5 m-3 m (8.2 ft-9.84 ft), 100 liter (26 gal)/min; MIL-STD-810F, Method 512.4, Procedure I, IEC-529, IP67
Drop . . . . .	26 drops at room temperature from 1.22 m (4 ft) onto plywood over concrete 6 additional drops at -30 °C (-22 °F) 6 additional drops at 60 °C (140 °F) MIL-STD-810F, Method 516.5, Procedure IV
Vibration . . . . .	General Minimum Integrity and Loose Cargo test MIL-STD 810F, Method 514.5, Procedure I, II
Operating Temperature . . . . .	-30 °C to 60 °C (-22 °F to 140 °F) MIL-STD 810F, Method 501.4, Procedure II
Storage Temperature . . . . .	-40 °C to 70 °C (-40 °F to 158 °F) MIL-STD 810F, Method 501.4, Procedure I MIL-STD 810F, Method 502.4, Procedure I, II, III
Temperature shock . . . . .	-35 °C/+65 °C (-31 °F/149 °F) MIL-STD-810F, Method 503.4, Procedure I
Humidity . . . . .	90%RH temp cycle 0 °C/+70 °C (32 °F/158 °F) MIL-STD-810F, Method 507.4
Altitude . . . . .	4572 m (15,000 ft) at 23 °C (73 °F) and 12,192 m (40,000 ft) at -30 °C (-22 °F) MIL-STD-810F, Method 500.4, Procedures I, II, III

### ELECTRICAL

Processor . . . . .	Marvell PXA320 XScale 806 MHz
Memory . . . . .	128 MB DDR SDRAM; ~30 MB reserved
Storage . . . . .	512 MB to 2 GB onboard non-volatile NAND Flash; ~50 MB reserved
Expansion . . . . .	1x SD/SDHC slot (all models), 1x Type II CF slot (900B)
Display . . . . .	480 x 640 pixel (VGA) 16-bit color TFT with LED backlight
Batteries . . . . .	5200 mAh Li-Ion rechargeable pack*
I/O . . . . .	USB Host and client, power, audio jack
Radios . . . . .	Bluetooth 2.0 + EDR; WLAN: WiFi (CCX) 802.11b/g WWAN: Quad-band GSM GPRS/EDGE

### NOTICE TO OUR EUROPEAN UNION CUSTOMERS

For product recycling instructions and more information, please go to [www.spectraprecision.com/ev.shtml](http://www.spectraprecision.com/ev.shtml).

#### Recycling in Europe:

To recycle Spectra Precision WEEE (Waste Electrical and Electronic Equipment products that run on electrical power), call +31 497 53 24 30, and ask for the "WEEE Associate". Or, mail a request for recycling instructions to: Spectra Precision, c/o Menlo Worldwide Logistics, Meerheide 45, 5521 DZ Eersel, NL.

*To ensure best performance when temperatures are below -20 °C (-4 °F), be sure battery is inserted in the device only when in use. When device is not in use at these temperatures, keep batteries in a pocket or stored in a warmer area.*

*Specifications are subject to change without prior notice.*



Head Office - Centurion (Gauteng)  
Tel: +27 12 683 4500  
E-mail: [info@optron.com](mailto:info@optron.com)

WEBSITE: [www.optron.com](http://www.optron.com)

Cape Town (Western Cape)  
Tel: +27 21 421 0555  
Email: [capetown@optron.com](mailto:capetown@optron.com)

Durban (Kwazulu Natal)  
Tel: +27 31 566 6221  
E-mail: [durban@optron.com](mailto:durban@optron.com)

South Africa

© 2008-2010, Spectra Precision. All rights reserved. ActiveSync, Microsoft, Windows, and Windows Media are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks is under license. All other trademarks are the property of their respective owners. PN 022487-1408 (10/10)

**OPTRON**  
g e o m a t i c s

SPECTRA PRECISION AUTHORIZED DISTRIBUTION PARTNER